

Tiger Canyon i7 - Board

A leap forward in Business Performance

Boundary-breaking performance is available with the latest 11th Gen Intel® Core™ i7 processors with Iris® Xe graphics and support for highspeed 3200 MHz DDR4 memory. Whether you're creating a digital kiosk, deploying intelligent vending, or refreshing enterprise PCs, Tiger Canyon can get the job done easily. Select Tiger Canyon SKUs also feature Intel vPro® technology for remote manageability, hardwareenhanced security features, and platform stability to help businesses cut IT costs and boost uptime.

More Performance. More Connections

Every Intel NUC 11 Pro system can support one 8K or four 4K displays for digital signage, video conferencing, and other deployments. Businesses can get more work done anytime, anyplace, with the latest wired and wireless options, like Intel® Wi-Fi 6 AX201, the fastest generation of Wi-Fi, and two ultra-fast Thunderbolt™ ports.

Build embedded solutions

Tiger Canyon, built on Intel 11th Gen architecture, provides greater system performance over previous generations with advanced hyperthreading technologies driving faster speeds and enhanced graphics. Qualified for 24x7 operation and backed by a three-year warranty, Intel NUC 11 Pro boards are small, powerful systems designed to meet today's needs-and keep businesses running for years. With Intel® vPro™ technology you can help your customers get ahead of security threats. The built-in hardwareenhanced security means you can keep client data and credentials secure, and remote manageability is perfect for installations such as unattended digital kiosks and intelligent vending.

Highlighted features

- 11th Gen Intel® Core™ i7-1165G7
- Intel® Xe Graphics
- Intel[®] vPro[®] Technology (1185G7 only)
- Two DDR4-3200 SO-DIMM Sockets
- M.2 Socket Supports PCIe Gen 4 SSDs
- M.2 Socket Supports SATA SSDs
- M.2 Socket Supports Wi-Fi
- Two HDMI 2.0b Supporting 4K @ 60Hz
- Intel® 2.5 Gigabit LAN
- One Thunderbolt 4 Port
- One Thunderbolt 3 Port
- Three USB 3.2 Gen 2 Ports
- One USB 2.0 Port
- Digital Audio 7.1 Surround Sound
- TPM 2.0

Customization

- 11th Gen Intel® Core™ i7 1185G7 (vPro)
- Supports DDR4 RAM 4GB-64GB
- Primary M.2 22x80 SSD 128GB-8TB
- Secondary M.2 22x42 Supports SSD 128GB-8TB
- One M.2 22x30 Supports Wi-Fi Module
- Two USB 2.0 Internal Headers
- One RS-232 Serial Internal Header



Simply NUC Services

You can order this NUC in your various configurations, as well as your corporate OS Image loaded and ready to deploy.

Simply MUC[®] (intel[®] Technology Provider

Technical Specifications

 Processors Intel® Core™ i7-1185G7 vPro processor (3.0GHz@28W, up to 4.8GHz Turbo, 4 Cores, 8 Threads, 12MB L3 Cache) Or 11th Gen Intel® Core™ i7 1165G7 processor (2.8Ghz@28W, up to 4.7Ghz Turbo, 4 Cores, 8 Threads, 12MB Cache) 	Graphics • Intel® Iris ™ Xe Graphics • Two HDMI 2.0b Ports with HDCP 2.2 • Built-in CEC for Both Ports • Support for a 3 rd and 4 th Monitor via Thunderbolt 4 with DisplayPort Peripheral Connectivity	System Memory • Two DDR4 SO-DIMM sockets, 64GB Max, 3200Mhz, 1.2V
		System Bios • 64 Mb Flash EEPROM with Intel® Platform Innovation Framework for EFI Plug and Play • Intel® Visual BIOS • Intel® Express BIOS Update Support
	 Intel® 2.5 Gigabit LAN w/ AMT Support (AMT is vPro only) Three Super-Speed USB 3.2 Gen 2 Ports (Two Front and One Rear) One Rear USB 2.0 Port Two Rear USB 3.2 Gen 2 Ports on Type-C Connector (One Thunderbolt 4; One Thunderbolt 3) One 22X30 M.2 Socket Supporting Wi-Fi Modules 	
Storage Capabilities • Primary M.2 22x80 Socket Supports M.2 SSDs, PCIe Gen 4		
M.2 SSDS, PCIe Gen 4 • Secondary M.2 22x42 Socket Supports SATA SSD		Front Panel Header • Vcc5/1A, 5Vsby2A, 3.3Vsby/1A
Audio • Up to 7.1 Multichannel (or Dual 8-channel) Digital Audio via HDMI		
 Hardware Management Features Trusted Platform Module (TPM) 2.0 AMT Supported Ethernet Controller Voltage and Temperature Sensing ACPI-compliant Power Management Control 		Expansion Capabilities • Two USB 2.0 Ports on Two 1x4
	Baseboard Power Requirements • 19V, AC-DC Power Adapter with Detachable Power Cord	Internal Headers • Two Consumer Electronics Control Headers
 Processor Fan Speed Control Fan Sensor Inputs Used to Monitor Fan Activity 	Board Dimensions • 4.09" x 4.01" • 104mm x 102mm	
Certification and Regulations		
Product Safety Regulations and Standards • IEC 60950-1	EMC/RF Regulations and Standards (Class B) • FCC CFR Title 47, • ETSI EN 501 489-17 Chapter I, Part • ETSI EN 501 895	Environmental Regulations RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU

China RoHS

Certified Operating Systems

- Windows 10 64-bit (Pro & Home)
- Windows 10 IoTe
- Windows Server 2019
- Linux (Fedora)

Environment Operating Temp

• CAN/CSA-C22.2 No. 60950-1

• 0° C to +40° C

• UL 60950-1

• EN 60950-1

• Non-Condensing Humidity

15, Subparts B, C, E • EN 62511 • CISPR 52 • AS/NZS 2772.2 • ICES-005 • AS/NZS 4268

• VCCI V-2, V-5, V-4

• KN-52

- EN 55052 EN 55024
- ETSI EN 500 528 KN-24
- ETSI EN 501 489-1 CNS 15458